

Technical Sheet		<b>BLFE-9D</b>		Nitta Corp. of America		
A-03				11/5/96		
ITEM		DESCRIPTION				
<b>Belt Specs</b>	Structure	<p>Non-Woven Fibers* (black) - 1.0mm thick</p> <p>2.5 mm</p> <p>Woven Polyester Fabric</p>				
	Anti-Static	YES				
<b>Manuf. Standard</b>	Size	Width	: 1829 mm	72 in		
		Length	: 100 m	328 ft		
<b>Belt Properties</b>	Tensile Strength	90 N/mm		514 lbs/in		
	Elongation at Break	12 %				
	Standard Tension	0.5 %				
	Working Load @ 0.5%	8 N/mm		46 lbs/in		
		Min. Pulley Diameter	Finger Joint : N/A		N/A	
	Skiver Joint : 25 mm		1 in			
	Temperature Range	Continuously: -20 to +70 °C		-4 to 158 °F		
		Periodically : -20 to +121 °C		-4 to 250 °F		
	Coefficient of Friction (Steel)	top: 0.3 to 0.35				
		Bottom : 0.3 to 0.35				
Weight	1.8 kg/m <sup>2</sup>		0.36 lbs/ft <sup>2</sup>			
Special Properties	Excellent Oil & Cut Resistance					

Phone: (800) 221-3689  
 Fax: (770) 623-1398

[www.nitta.com](http://www.nitta.com)

Phone: (800) 221-3689  
Fax: (770) 623-1398

[www.nitta.com](http://www.nitta.com)