

Technical Sheet		CC-12AKTR		Nitta Corp. of America		
C-016		(CC-12ATR)		rev.-31-Jan-03		
ITEM		DESCRIPTION				
Belt Specs	Structure	<p>PVC (white) - 90° shore A - 0.5mm thick</p> <p>2.1 mm</p> <p>PVC layer</p> <p>Polyester Fabric (white)</p>				
	Anti-Static	NO				
Manuf. Standard	Size	Width: 2000 or 3000 mm	78 or 118 in			
		Length: 100 m	328 ft			
Belt Properties	Tensile Strength	80 N/mm		457 lbs/in		
	Elongation at Break	12 %				
	Standard Tension	0.5 %				
	Working Load at 1%	8 N/mm		46 lbs/in		
	Min. Pulley Diameter	Finger Joint :	100 mm		4.0 in	
		Skiver Joint :	100 mm		4.0 in	
	Temperature Range	Continuously:	-10 to +70 °C		14 to 158 °F	
		Periodically :	-20 to +100 °C		-4 to 212 °F	
	Coefficient of Friction (Steel)	top:	0.3 to 0.4			
		bottom:	0.2 to 0.25			
Weight	2.5 kg/m ²		0.51 lbs/ft ²			
Special Properties	Cut Resistant, Wood industry belt					

Phone: (800) 221-3689

www.nitta.com

Fax: (770) 623-1398